

Study of second generation sugarcane bioethanol viability through integrated process optimization

Furlan, F.F.¹, Costa, C. B. B.¹, Cruz, A. J. G.¹, Fonseca, G. C.¹, Secchi, A. R.², Soares, R. P.³, Giordano, R. C.¹

¹Federal University of São Carlos, Brazil; ²Federal University of Rio de Janeiro, Brazil; ³Federal University of Rio Grande do Sul, Brazil

Introduction

Sugarcane biomass can be exploited in order to increase the production of bioethanol, produced in Brazil from sugarcane juice. The second generation process, whichever technology is selected to be implemented, must be integrated to the first generation production process, in order to reduce costs and increase biofuel competitiveness. Nevertheless, the integration of a second generation plant to the first generation one poses a process challenge, since the whole process must be energetically self-sufficient, besides exhibiting economic advantages over the conventional first generation industry. The combustion of sugarcane bagasse is responsible in these plants for the energetic supply (steam and electric power), and any energy surplus is sold to electric power companies. When part of bagasse is diverted to lignocellulosic ethanol production, the energetic demand of the integrated process must be precisely evaluated. Furthermore, if enzymatic hydrolysis is selected, enzyme costs play important role. Hence, the fraction of bagasse diverted to hydrolysis becomes a key parameter in process economics.

In the present work, an integrated first and second generation bioethanol from sugarcane plant is simulated using the applicative Environment for Modeling, Simulation and Optimization (EMSO, www.enq.ufrgs.br/trac/alsoc/wiki/EMSO) and the Particle Swarm Optimization (PSO) algorithm is used to optimize the process, in terms of maximizing plant profit, having the many demands of the plant as constraints. In this way, the fraction of bagasse diverted to hydrolysis is constrained to the energetic self-sufficiency of the plant. The second generation technology here makes use of enzymes to hydrolyze cellulose and hemicelluloses of pretreated bagasse. Lignin is burned, contributing to energy supply. Since prices of enzymes, ethanol, electricity and the surplus bagasse (sold as process residue for animal feed) impact on the viability of the integrated process, different economic scenarios are studied.

Results and Conclusions

The main result of the work is the developed tool, which joins simulation of the integrated process to optimization, in order to indicate the most profitable use of bagasse as a function of the market situation, considering process demands. In this way, the process may be properly adjusted to the most profitable operating condition.

Supported by Fundação de Amparo à Pesquisa do Estado de São Paulo - FAPESP

Author publications

Almeida Neto, E.; Secchi, A. R. (2011). Dynamic Optimization of a FCC Converter Unit: Numerical Analysis. Brazilian Journal of Chemical Engineering, v. 28, p. 117-136.

Beninca, M.; Trierweiler, J. O.; Secchi, A. R. (2011). Heat Integration of an Olefins Plant: Pinch Analysis and Mathematical Optimization Working Together. Brazilian Journal of Chemical Engineering, v. 28, p. 101-116.

Soares, R. P. (2011) The Combinatorial Term for COSMO-Based Activity Coefficient Models. *Industrial & Engineering Chemistry Research*, v. 50, p. 3060-3063.

Mendes, A. A.; Giordano, R. C.; Giordano, R. L. C.; de Castro, Heizer F. (2011). Immobilization and stabilization of microbial lipases by multipoint covalent attachment on aldehyde-resin affinity: Application of the biocatalysts in biodiesel synthesis. *Journal of Molecular Catalysis. B, Enzymatic*, v. 68, p. 109-115.

Santiago, P. A.; Giordano, R. C.; Suazo, C. A. T. (2011). Performance of a vortex flow bioreactor for cultivation of CHO-K1 cells on microcarriers. *Process Biochemistry*, v. 46, p. 35-45.

Furlan, F.F.; Giordano, R.C.; Cruz, A.J.G.; Costa, C.B.B. ; Secchi, A.R.; Soares, R.P.(2010). Bioprocess systems engineering applied to a multipurpose second generation ethanol-from-sugarcane plant: assessing the performance of local and global optimization algorithms. *Journal of Biotechnology*, v. 150, p. 398-399.

Furlan, F. F.; Gonçalves, J. A. S.; Henrique, V. M. ; Soares, R. P. ; Secchi, A. R.; Giordano, R. C. (2010). Método robusto para simulação de colunas de destilação em simuladores baseados em equações: o caso da purificação de bioetanol. In: COBEQ/EBA/CBTERMO 2010, Foz do Iguaçu. *Anais do COBEQ/EBA/CBTERMO 2010*. p. 3080-3087.

Mariano, A. P., Costa, C. B. B., Maciel, M. R. W., Maugeri Filho, F., Atala, D. I. P., Angelis, D. de F., Maciel Filho, R. (2010). Dynamics and Control Strategies for a Butanol Fermentation Process. *Applied Biochemistry and Biotechnology*. v.160, p.2424 - 2448.

Mariano, A. P., Costa, C. B. B., Angelis, D. F., Atala, D. I. P., Maugeri Filho, F., Wolf Maciel, M. R., Maciel Filho, R. (2010). Genetic Algorithms (binary and real codes) for the optimisation of a fermentation process for butanol production. *International Journal of Chemical Reactor Engineering*. v.8, A101.

Costa, C. B. B., Maciel Filho, R. (2010). Nanoparticle Processes Modelling: The Role of Key Parameters for Population Balances for On-Line Crystallization Processes Applications. *Powder Technology*. v.202, p.89 - 94.

Mariano, A. P., Costa, C. B. B., de Angelis, D. de F., Maugeri Filho, F., Atala, D. I. P., Wolf Maciel, M. R., Maciel Filho, R. (2010). Optimisation of a continuous flash fermentation for butanol production using the response surface methodology. *Chemical Engineering Research & Design*. v.88, p.562 - 571.

Mariano, A. P., Costa, C. B. B., de Angelis, D. de F., Maugeri Filho, F., Atala, D. I. P., Wolf Maciel, M. R., Maciel Filho, R. (2010). Optimisation of a fermentation process for butanol production by particle swarm optimisation (PSO). *Journal of Chemical Technology and Biotechnology*. v.85, p.934 – 949.

Melo, D. N. C., Costa, C. B B, Vasco de Toledo, E. C., Mariano, A. P., Wolf Maciel, M. R., Maciel Filho, R. (2010). Optimization of a Three-Phase Catalytic Slurry Reactor Using Reduced Statistical Models. *International Journal of Chemical Reactor Engineering*. v.8, A62.

Nucci, E. R.; Cruz, A. J. G.; Giordano, R. C. (2010). Monitoring bioreactors using principal component analysis: production of penicillin G acylase as a case study. *Bioprocess and Biosystems Engineering*, v. 33, p. 557-564.

Torres, R. C.; Jesus, C. D. F.; Cruz, A. J. G. (2010). Cristalização do açúcar: avaliação de estratégias de controle. *Revista C & I. Controle & Instrumentação*, v. 156, p. 25-32.

Cerri, M. O.; Baldacin, J. C.; Cruz, A. J.G. ; Hokka, C. O.; Badino, A. C.; (2010). Prediction of mean bubble size in pneumatic reactors. *Biochemical Engineering Journal*, v. 53, p. 12-17.

Cruz, A. J. G.; Gonzáles, E. A. U.; Zangirolami, T. C. (2010). Projeto Mirror: Um modelo para comparação e reconhecimento de cursos de engenharia química. *Revista Brasileira de Engenharia Química*, v. 26, p. 16-19.

Sousa, J.R. ; Correa, J.A.C. ; Martins, J.J.L. ; Melo, V.M.M. ; Cruz, A. J. G.; Gonçalves, L.R.B. (2010). A Kinetics Studies of the Production Rhamnolipids by *Pseudomonas aeruginosa* LAMI from Glycerin. *Journal of Biotechnology*, v. 150, p. 395-396.

Foramiglio, F.; Gonçalves, L. C. G.; Fonseca, G. C.; Cruz, A. J. G.; Jesus, C. D. F.; Dias, M. O. S.; Costa, C. B. B. (2010) Modelagem e simulação das operações de uma biorrefinaria de cana-de-açúcar utilizando software EMSO. In: Congresso Brasileiro de Engenharia Química, 2010, Foz do Iguaçu, PR. XVIII Congresso Brasileiro de Engenharia Química (COBEQ 2010), v. 1. p. 1039-1048.

Fonseca, G. C.; Secchi, A. R.; Giordano, R. C.; Cruz, A. J. G. (2010) Modelagem e simulação da etapa de fermentação no simulador de processos EMSO. In: Congresso Brasileiro de Engenharia Química (COBEQ 2010), 2010, Foz do Iguaçu, PR. XVIII Congresso Brasileiro de Engenharia Química (COBEQ 2010), v. 1. p. 2859-2868.

Rodrigues, R.; Soares, R. P.; Secchi, A. R. (2010). Teaching Chemical Reaction Engineering Using EMSO Simulator. *Computer Applications in Engineering Education*, v. 18, p. 607-612.

Staudt, P. B.; Soares, R.P.; A. R. Secchi; Cardozo, N. S. M. (2010). A New Cubic Equation of State for Prediction of VLE of Polymer Solutions. *Fluid Phase Equilibria*, v. 295, p. 38-45.

Domingues, T.L.; Secchi, A. R.; Mendes, T. F. (2010). Overall Efficiency Evaluation of Commercial Distillation Columns with Valve and Dualflow Trays. *AIChE Journal*, v. 56, p. 2323-2330.

Favero, J.L. ; Secchi, A.R. ; Cardozo, N.S.M. ; JASAK, H. (2010). Viscoelastic fluid analysis in internal and in free surface flows using the software OpenFOAM. *Computers & Chemical Engineering*, v. 34, p. 1984-1993.

FAVERO, J. ; A. R. SECCHI ; CARDOZO, N. S. M. ; JASAK, H. (2010). Viscoelastic Flow Analysis using the Software OpenFOAM and Differential Constitutive Equations. *Journal of Non-Newtonian Fluid Mechanics*, v. 165, p. 1625-1636.

Gerber, R. P.; Soares, R. P. (2010). Prediction of Infinite-Dilution Activity Coefficients Using UNIFAC and COSMO-SAC Variants. *Industrial & Engineering Chemistry Research*, v. 49,

p. 7488-7496.

Le Roux, G.A.C.; Reis, G. B. ; Jesus, C. D. F. ; Giordano, R. C. ; Cruz, A. J. G.; Moreira Jr, P.T.; Nascimento, C. A. O. ; Loureiro, L. V. (2010). Cooperative Weblabs: A tool for cooperative learning in chemical engineering in a global environment. *Chemical Engineering Education*, v. 44, p. 9-12.

Pinto, G. A.; Giordano, R. L. C.; Giordano, R. C. (2009). Remote engineering for a cheese whey biorefinery: an Internet-based application for process design, economic analysis, monitoring, and control of multiple plant sites. *Bioprocess and Biosystems Engineering*, v. 32, p. 69-78.

Mariano, A. P., Costa, C. B. B., Angelis, D. F., Maugeri Filho, F., Atala, D. I. P., Wolf Maciel, M. R., Maciel Filho, R. (2009). Optimization Strategies Based on Sequential Quadratic Programming Applied for a Fermentation Process for Butanol Production. *Applied Biochemistry and Biotechnology*. v.159, p.366 - 381.

Nucci, E. R.; Souza, V. R.; Silva, R. G.; Reis, G. B.; Giordano, R. L. C.; Giordano, R. C.; Cruz, A. J. G. (2009). On-line Monitoring of Penicillin G Acylase (PGA) Production Using a Fuzzy Logic Algorithm. *Chemical Product and Process Modeling*, v. 4, p. 1-11.

Nucci, E. R.; Cruz, A. J. G.; Giordano, R. L. C.; Giordano, R. C. (2009). Monitoring penicillin G acylase (PGA) production using principal component analysis (PCA). *Computer-Aided Chemical Engineering*, v. 27, p. 1629-1634.

Salau, N. P. G. ; Neumann, G. A. ; Trierweiler, J. O.; Secchi, A. R. (2009) . Multivariable Control Strategy Based on Bifurcation Analysis of an Industrial Gas-Phase Polymerization Reactor. *Journal of Process Control*, v. 19, p. 530-538.

Fisch, A. G.; Cardozo, N. S. M.; Secchi, A. R.; Stedile, F. C.; Livotto, P. R. ; de Sa, D. S. ; Rocha, Z. ; Santos, J. H. Z. (2009). Immobilization of Metallocene within Silica Titania by a Non-hydrolytic Sol Gel Method. *Applied Catalysis. A, General*, v. 354, p. 88-101.

Diehl, F. C. ; Secchi , A. R.; Lusa, L.P.; Muniz, L. A. R.; Longhi, L. G. S. (2009). Simulação Operacional de uma Torre de Destilação Atmosférica via Aspen Plus e Avaliação de Modelos de Analisadores Virtuais. *Controle & Automação*, v. 20, p. 305-322, 2009.

Souza, C. F. V.; Faccin, D. J. L.; Mertins, O.; Heck, J. X.; Silveira, N. P.; Secchi, A. R. ; Ayub, M. A. Z. (2009). Kinetics of thermal inactivation of transglutaminase from a newly isolated *Bacillus circulans* BL32. *Journal of Chemical Technology and Biotechnology*, v. 1, p. 1-9.

Faccin, D. J. L.; Martins, I.; Cardozo, N. S. M. ; Rech, R. ; Ayub, M. A. Z. ; Moitinho, T.L.A.; Gambetta, R.; Secchi, A. R. (2009). Optimization of C:N ratio and minimal initial carbon source for Poly(3-hydroxybutyrate) production by *Bacillus megaterium*. *Journal of Chemical Technology and Biotechnology* (1986), v. 84, p. 1756-1761.

Fisch, A. G.; Cardozo, N. S. M.; Secchi, A. R.; Stedile, F. C.; Radtke, C.; de Sa, D. S.; Rocha, Z.; Santos, J. H. Z. (2009) . Immobilization of Zirconocene within Silica-Tungsten by Entrapment: Tuning Electronic Effects of the Support on the Supported Complex. *Applied Catalysis. A, General*, v. 370, p. 114-122.

Staudt, P. B.; Soares, R. P. (2009). Reliability vs. Efficiency When Solving Multiphase Equilibrium Problems with Hybrid Optimization Codes. *Computer-Aided Chemical Engineering*, v. 27, p. 585-590.

Cabrerapadilla, R ; Pinto, G; Giordano, R; Giordano, R (2009). A new conception of enzymatic membrane reactor for the production of whey hydrolysates with low contents of phenylalanine. *Process Biochemistry*, v. 44, p. 269-276.

Galvao, C.; Pinto, G.; Jesus, C. D. F.; Giordano, R. C.; Giordano, R. L. C. (2009) . Producing a phenylalanine-free pool of peptides after tailored enzymatic hydrolyses of cheese whey. *Journal of Food Engineering*, v. 91, p. 109-117.

Trovati, J.; Giordano, R. C.; Giordano, R. L. C. (2009). Improving the Performance of a Continuous Process for the Production of Ethanol from Starch. *Applied Biochemistry and Biotechnology*, v. 156, p. 76-90.

Da Silva, A.J. ; Horta, A.C. ; Iemma, M. ; Novo, M.T. ; Zangirolami, T.C. ; Giordano, R. (2009). Production of potential subunit vaccine against swine erysipelas in fed-batch cultures of *E. coli* BL21(DE3). *New Biotechnology*, v. 25, p. S223-S223, 2009.

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.