

# **SUGARCANE BAGASSE PARTICLES SIZE USED IN ENZYMATIC HYDROLYSIS IN THE LITERATURE AND OBTAINED BY A PNEUMATIC CLASSIFYING EQUIPMENT**

**Almeida, E.1; Silva, M. A.1;; Cortez, L.A.B.2; Roca, G.A.A.3; Olivares, E.G.4**

1 - Faculdade de Engenharia Química – FEQ, Universidade Estadual de Campinas- UNICAMP, Brasil, 2 - Faculdade de Engenharia Agrícola – FEAGRI, Universidade Estadual de Campinas – UNICAMP, Brasil; 3 - Centro de Estudios de Eficiencia Energética - CEEFE, Universidad de Oriente, Santiago de Cuba, Cuba; 4 - Laboratório Nacional de Ciência e Tecnologia do Bioetanol – CTBE, Brasil

## **Introduction**

The main objective of the physical pretreatment of the biomass is to reduce the particle size so as to increase the surface contact area and obtain a homogeneous material ideal to use in several energy conversion processes. Some operations often used for this purpose are milling, grinding and chipping or a combination of these.

The increase of contact surface area and homogenization of the material allow obtaining, for example, higher yield of hydrolysis, varying with the biomass type, hydrolysis type and duration of operation.

However, the main barrier to using these types of pretreatment on a large scale is related to continuing operation and the high energy expended, as the price of energy increases continuously, this process still ends up being economically unfeasible.

In this context it was developed new equipment that permits a continuous separation of sugarcane bagasse fractions with different particles size, which can decrease the energy consumption. Basically the operate principle of the pneumatic classifier is based on solid particles fluidization, elutriation and pneumatic transport within an air column. The fine particles are dragged and collected in a cyclone at the top of the equipment, the medium particles circulating in the column are collected through an opening next to the middle of this and the coarse particles, heavy enough to not be either dragged or put into lifting, fall by gravity action into an opening at the bottom of the air column.

Thus, the scope of this paper is to compare the particle size reduction pretreatment used in enzymatic hydrolysis experiments available in the literature with particles size obtained by pneumatic classifier.

## **Results and conclusions**

Aiming assessment how the researchers are conducting physical pretreatments to study enzymatic hydrolysis was carried out a search on SCOPUS basis with the listed sequence of key words: ((TITLE-ABS-KEY(hydrolysis) AND TITLE-ABS-KEY(sugarcane) AND TITLE-ABS-KEY(bagasse))) AND ((ethanol)) AND (enzyme).

This search was performed on 16/08/2010 and resulted in 98 articles written since 1985 to 2010, they were organized considering particle size of sugarcane bagasse to enzymatic hydrolysis.

Organizing the articles by particle size of sugarcane bagasse the first finding was that only forty five from ninety eight articles had the caution to describe the particle size of sugarcane samples used in experiments. This is an important observation since it

shows some researchers don't are worried with basic characteristics of biomass which could influence on hydrolysis yields.

Focusing only on articles that informed the particle size of sugarcane bagasse it was observed:

- Ten used particle size smaller or equal than 0.50 mm;
- Fourteen used particle size bigger than 0.50mm and smaller or equal than 1.00mm;
- Eleven used particle size bigger than 1.00mm and smaller or equal than 2.00mm;
- Ten used particle size bigger than 2.00mm;

The data evaluation allows concluding a remarkable standard absent and it represents a difficulty to assess different pretreatment methods. Refining the search was observed from forty five articles, which described particle size of sugarcane bagasse, twenty seven of them studied enzymatic hydrolysis, the others investigated either pretreatment methods or other subjects like acid hydrolysis, xylanase production etc.

From these twenty seven articles, nineteen carried out particles size reduction and the other eight performed sieving of sugarcane bagasse samples before experiments. These nineteen articles performed particle size reduction by milling but only seven described in details the used equipments.

This lack of information difficults not only the reproducibility of the experiments by other researchers but also the results comparison.

From eight articles that performed sieving the particle size distribution were:

- Three used particle size whose values range between 0.14 to 0.25mm;
- Three used particle size whose values range between 0.45 to 0.90mm;
- Two used particle size whose values range between 2.20 to 10.00mm;

One final observation is that fourteen articles from twenty seven informed the equilibrium moisture content of sugarcane bagasse used in experiments, varying from 5 to 10% (w.b.) according to the environmental conditions.

Experiments conducted in the pneumatic classifier with sugarcane bagasse dried at equilibrium moisture content, range from 7% to 10% (w.b.), with feed of 18.76kg sugarcane bagasse / h and column air flow of 88m<sup>3</sup>/h showed the following results:

- Fine Fraction: particle mean diameter range from 0.52 to 0.54mm, consisting at about 25% to 26% of total bagasse classified;
- Medium Fraction: particle mean diameter range from 0.77 to 0.81mm, consisting at about 6% to 7% of total bagasse classified;
- Coarse Fraction: particle mean diameter range from 3.80 to 4.25mm, consisting at about 68% to 69% of total bagasse classified;

From the articles in which particle size reduction was performed and the particle size range was described, 77% used the particles size in the range correspondent to the fine and medium fractions, that is, around 30% of the classified sugarcane bagasse. Nevertheless, this result was reached without the need of milling, grinding or chipping, which are energo-intensive operations.

It is important to remark that varying the solids feed and air flow in the column bigger or smaller proportions of the classified fractions can be obtained, also occurring more or less variation in the average particles diameter. It is possible to adjust the operation conditions in order to achieve sugarcane bagasse with the desired characteristics.

We conclude that is almost impossible to compare yields obtained from enzymatic hydrolysis experiments with respect to particle size because there isn't a standard.

The literature review pointed out the importance to use small particles size in experiments but none of the reviewed articles determined the particle size range to reach the better hydrolysis yields.

This way it would be interesting further research in order to find the best particle size range for enzymatic hydrolysis of sugarcane bagasse, such range is dependent on the other pretreatments used prior the hydrolysis itself. The pneumatic classifier which works continuously and consumes low energy appears as a new alternative to achieve this goal.

*Supported by FAPESP – Fundação de Amparo à Pesquisa do Estado de São Paulo, Brazil*

## Authors publication:

### Eduardo de Almeida

1 - GÓMEZ, Edgardo Olivares; SOUZA, Renata Torres; ROCHA, George Jackson de Moraes; ALMEIDA, Eduardo; CORTEZ, Luís Augusto Barbosa. A palha de cana-de-açúcar como matéria-prima para processos de segunda geração. In: CORTEZ, L. A. B. (Organizador). **Bioetanol de Cana-de-Açúcar: P&D para Produtividade e Sustentabilidade**. São Paulo, SP: Editora Blucher, 2010.992p.

2 - GÓMEZ, Edgardo Olivares; ALARCÓN, Guillermo Alfonso Roca; CORTEZ, Luís Augusto Barbosa; ALMEIDA, Eduardo; OLIVEIRA, Bruno Rodrigues; ROCHA, George Jackson de Moraes. **Estudo experimental da classificação pneumática contínua de bagaço de cana-de-açúcar**. In: 8º Congresso Internacional sobre Geração Distribuída e Energia no Meio Rural – AGRENER GD 2010. Campinas, 2010.

### Maria Aparecida Silva

1. SOSA-ARNAO, Juan Harold, CORRÊA, Jefferson Luiz Gomes, SILVA, Maria Aparecida, NEBRA, Silvia Azucena. Sugar cane bagasse drying - a review. **International Sugar Journal**. , v.108, p.381 - 386, 2006.

2. SERENO, Alberto M., SILVA, Maria Aparecida, MAYOR, Luis. Determination of Particle Density and Porosity in Foods and Porous Materials with High Moisture Content. **International Journal of Food Properties**. , v.10, p.455 - 469, 2007.

### Edgardo Olivares Gómez

1 – LEITE, Rogério César de Cerqueira (coordenador). **Bioetanol Combustível: uma Oportunidade para o Brasil**. 1. ed. Brasília, Brasil: Centro de Gestão em Estudos Estratégicos - CGEE, 2009. v. 01. 536 p.

2 – CORTEZ, Luís Augusto Barbosa, LORA, Electo Eduardo Silva, GÓMEZ, Edgardo Olivares. **Biomassa para Energia**. 1. ed. Campinas: Editora da UNICAMP, 2008. v. 1.736 p.

3 - SANTOS, W.D.; GÓMEZ, E. O.; BUCKERIDGE, M.S. Part I - Chapter 2 - Bioenergy and the Sustainable Revolution. In: M.S. Buckeridge and G.H. Goldman. (Org.). **Routes to Cellulosic Ethanol**. 01 ed. New York: Springer Science+Business Media, LLC, 2011, v. 01, p. 15-26.

4 - GÓMEZ, Edgardo Olivares; SOUZA, Renata Torres; ROCHA, George Jackson de Moraes; ALMEIDA, Eduardo; CORTEZ, Luís Augusto Barbosa. A palha de cana-de-açúcar como matéria-prima para processos de segunda geração. In: CORTEZ, L. A. B.

(Organizador). **Bioetanol de Cana-de-Açúcar: P&D para Produtividade e Sustentabilidade**. São Paulo, SP: Editora Blucher, 2010.992p.

5 - SOUZA-CORRÊA, J.A. ; PIMENTA, M.T.B. ; ROCHA, G. J. M. ; GÓMEZ, E. O. ; SQUINA, F. M. ; CURVELO, A.A.S. ; FILHO, J.A. . Hydrothermal and Atmospheric Pressure Microplasma Pretreatment Processes of Sugarcane Bagasse. In: Elena Tatarova; Vasco Guerra; Evgenia Benova; Andre Ricard. (Org.). **Plasma for Environmental Issues** (Proceedings of the 2nd International Workshop at the 36th European Physical Society Conference on Plasma Physics, July 02-03, 2009, in Sofia, Bulgaria). 01 ed. Sofia, 2010, p. 68-76.

6 - ROCHA, G. J. M.; BARBOSA, M.T.B.P.; GÓMEZ, E. O.; OLIVEIRA, B.R.; REZENDE, C.C.; DRIEMEIER, C.E.; CORREA, J.A.S.; FILHO, J.A.; ROSSELL, C.E.V. **Pré-Tratamentos Físico-Químicos do Bagaço de Cana-De-Açúcar para Hidrólise Enzimática**. ALCOOLBras, São Paulo, Brasil, 30 abr. 2010.

7 - ROCHA, G. J. M.; GONÇALVES, A.R.; OLIVEIRA, B.R.; GÓMEZ, E. O.; ROSSELL, C.E.V. **Compositional Variability of Raw, Steam Exploded and Delignified Sugarcane Bagasse**. In: 8º Congresso sobre Geração Distribuída e Energia no Meio Rural, 2010, Campinas, São Paulo, Brasil. Anais do 8º Congresso sobre Geração Distribuída e Energia no Meio Rural, 2010.

8 - GÓMEZ, E. O.; ROCA, G.A.A.; CORTEZ, L. A. B.; ALMEIDA, E.; OLIVEIRA, B.R.; ROCHA, G. J. M. **Estudo experimental da classificação pneumática contínua de bagaço de cana-de-açúcar**. In: 8º Congresso sobre Geração Distribuída e Energia no Meio Rural - AGRENER 2010, 2010, Campinas, São Paulo, Brasil. Anais do 8º Congresso sobre Geração Distribuída e Energia no Meio Rural - AGRENER 2010. Campinas, 2010.

9 - SQUINA, F. M.; PRADE, R. A.; MURAKAMI, M. T.; GÓMEZ, E. O.; PRADELLA, J. G. C.; ROSSELL, C.E.V. **Development of a Library for Biomass-Conversion Enzymes**. In: XVII Simpósio Nacional de Bioprocessos, 2009, Natal/RN. Anais do XVII Simpósio Nacional de Bioprocessos, 2009.

10 - BORGES, R. A.; SQUINA, F.; GÓMEZ, E. O.; ROSSELL, C.E.V.; PRADELLA, J. G. C. **Análise por Microscopia Eletrônica de Varredura da Desconstrução de Fibra de Bagaço de Cana-de-Açúcar tratada com Enzima Celulolítica Comercial**. In: XVII Simpósio Nacional de Bioprocessos, 2009, NATAL/RN. Anais do XVII Simpósio Nacional de Bioprocessos, 2009.

11 - ULLMANN, M.A.; SANTOS, L.V.; PIMENTEL, V.L.; FILHO, J.A.; ROCHA, G. J. M.; GÓMEZ, E. O.; MEDEIROS-RIBEIRO, G.; ZERI, A.C. **Isolamento e Visualização por AFM de Microfibras Nanoestruturadas do Resíduo Processado De Saccharum Officinarum L.**In: 19o RAU - Reunião Anual de Usuários do LNLS - Laboratório Nacional de Luz Síncrotron, 2009, Campinas, São Paulo, Brasil. Livro de Resumos, 2009.

12 - ROSSELL, C.E.V.; PRADELLA, J. G. C.; GÓMEZ, E. O.; SQUINA, F. M. **Physical Conditioning Unit of the Sugarcane Biomass Feedstock: Sugarcane Bagasse and Sugarcane Trash.** In: Workshop on Hydrolysis Route for Cellulosic Ethanol from Sugarcane. Campinas, 2009.

This document was created with Win2PDF available at <http://www.win2pdf.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.  
This page will not be added after purchasing Win2PDF.